2914222

BAIC

SRZGRR Sazgar Engineering Works Limited Head Office: 88-Ali Town, Thokar Niaz Baig, Raiwind Road, Lahore, Pakistan. Ph: +92-42-35291573-4, 35297861-2, Fax: +92-42-35297863 Email: info@sazgarautos.com







Born For Excellence

King of SUVs with a dominating presence

Based on the famous BJ212, the BJ40 Plus is designed as a thoroughbred SUV. An embodiment of simple, strong and imposing features. Its dashing profile is a perfect confluence of toughness, elegance and sophistication.



Robust & Fearless



Dedicated Off-Road Instrumentation

The dashboard displays all essential information such as gradient, direction, altitude and atmospheric pressure; so drive with ease and travel care free.

Smart Functions

The operation of BJ40 Plus is easy and convenient by virtue of ergonomic design and attention to detail, e.g. cup holders, panoramic reversing radar, powered foldable side mirrors and overhead stereo

Customized functions to resonate with your personality

Embark on your dream adventures with the new BJ40 Plus. Embrace new challenges in your travels with confidence.



Multiple Body Configurations

The roof, doors and windscreens are easily detachable. BJ40 Plus offers the unique ability to adapt perfectly to any situation.

Oversized Trunk Space

The seats can be folded as needed.When the rear seats are collapsed, you may have a storage up to 600L.

Explore The Unknown

Ultimate performance for the drive of your life

Venture into the uncharted with unquestionable reliability of the BJ40 Plus. This extraordinary SUV boasts unbridled power, opening roads to new horizons.

Selectable 4x4-Drive Modes

BJ40 Plus performs under all kinds of weather and through all terrain. 4L mode magnifies torque 2.5 times to a hefty 542NM.

- 2H 2-wheel rear-drive
- 4H High-speed 4-wheel drive
- Low-speed 4-wheel drive



Strong Separate Frame Construction BJ40 Plus boasts a separate frame construction, which increases its torsional stiffness by 40%. The cross section of the frame beam is



Safe and Reliable A standard configuration of ultra-high anti-roll frame in the front and rear angle is 33°, ramp-over angle is 24°, constitutes a natural barrier to protect and the min. ground clearance is passengers and ensures safety. The 210mm. anti-compressive stiffness of the roof is up to 22240N.



High-efficiency power output: Reaches 82% of peak torque at 1200rpm and 90% at 1600rpr









Luxurious & Comfortable

The BJ40 Plus is manufactured and tested as a military vehicle, with a comparable set of attributes. It is the perfect choice for a safe and secure, yet exhilarating experience.



Built tough for a carefree and thrilling ride

Built diligently with a robust design to cater to your adventurous lifestyle. Dare to venture on a riveting journey with the BJ40 Plus.





To Military Standard

This SUV employs military technology, e.g. metal brake lines and all-floating drive axle

Tested like a military Vehicle BJ40L Plus has successful passed a road test of over one million kilometers.

1.1 MILLION KM tested as a military vehicle



BJ4. - PLUS SPECIFICATIONS

BJ40 right-hand version-	Honorable Edition 2.0-6AT
nction definition configuration	2.0-6AT
Basic Parameters	Gasoline
neight mm	4645*1925*1871
	2745
el base mm	1610/1610
le (°)	37
າ	31
ing angle (°)	23
clearance mm	210
diameter M	12.5
	75
	5
nt %	60
	2080
	Body-chassis frame
	Part-time 4WD
n system	Double wishbone I coil spring independent suspension
system	Five-link/ coin-spring dependent suspension
e type	Vented Disc/ Disc
ystem	Hydraulic power assistance
,	265 I 65 R17
Engine	Gasoline
Liigino	4G20TI3
nent ml	1981
ient im	6AT
KW/BHP	160/215
Nm/rmp	320/1750-4500
Km/h	160
	95 Gasoline
gear	•
	China V
r	•
orake / accelerator pedal	•
Chassis	Gasoline
oster	•
	•
rake EPB	•
nitoring	•
	•
railer	•
Interior trim	Gasoline
	•
nandle	•
st 4 / 6 fold / Flip forward	•
	•
Stener (4)	•
	AUX + USB
stment direction and mode	• 4-way manual
seat adjustment direction and mode	4-way manual
front passenger / rear seat	Fabric
2+ rear 3	•
senger airbag	•
senger not wearing seat belt reminded	•
ing force-limiting three-point safety belt	•
	•
zelt	•
pelt	
lock	· · · · · · · · · · · · · · · · · · ·

Dimensions



1 Approach angle 36°

- 2 Ramp angle 24°
- 3 Departure angle 34°
- 4 Min. ground clearance 210mm

For more details, please visit www.sazgarbaic.com.

This brochure is published by Sazgar Engineering Works Limited. All figures and presentations may be amended from time to time. We reserve the rights of final explanation. Due to product design or improvement, etc., we reserve the rights to amend the models and service specified herein, without giving further notice. The parameters and configurations shall be subject to the actual products.